BC-10



Now you can make your own business cards in your office so easily, quickly and accurately!

Our Business card cutting machine: BC-10 that works alongside any high quality digital photocopying or printing device to produce a professionally cut business cards automatically, easily and fast.

The BC-10 can cut the pages into business cards with unbelievable ease, speed, and accuracy.

Whether your a small business or large corporation producing 1,000s of cards a day, the cutting edge innovations being applied to the UCHIDA BC-10 Business Card Cutter will satisfy your every need.

You will be able to eliminate the need to outsource business cards to printing companies thus reducing overhead costs.



cards on one sheet

is done by PC










optional perforation and scoring device

Optical perforation device or scoring device can be easily installed in place of the cutter device for







perforation


NEW


UCHIDA


MULTI CARD CUTTER


Versa Trim


All job can do one Box From Uchida











Specifications	BC-10	VersaTrim
Paper quality	110-300g / m² (0.15-0.30mm) * 1	120-350g / m² (0.13-0.35mm) *2
Cutting Speed	100 Business cards / min.	100 Business cards / 78 sec.
Stacking capacity of Paper Feed tray	50 sheets (In case of sheet thickness of 0.2mm)	50 sheets (In case of sheet thickness of 0.2mm)
Counter	Addition or preset subtraction is selective	Addition or preset subtraction is selective
Dimensions	585(W) x 428(D) x 325(H) mm (23.0" x 16.9" x 12.8")	750(W) x 435(D) x 290(H) mm (2.9" x 1.7" x 1.2")
Net weight	21.0Kg (46.3 lbs)	24 kg (52.9 lbs)
Voltage	220-240V AC 50/60Hz or 100-120V AC 50/60Hz	220-240V AC 50/60Hz or 100-120V AC 50/60Hz
Power consumptions	32W/0.44Amp (220-240V machine), 27W/0.4Amp (100-120V machine)	44 W / 0.47 Amp (220-240 V machine)
Error detection	Paper jam, cut mark detection error, no slitter unit, top cover opened and no waste box	Paper jam, cut mark detection error, no slitter unit, top cover opened and no waste box
Optional Unit	Slitter unit, perforation unit, scoring unit	Slitter unit, perforation unit, scoring unit
Safety standards	CE (European version) or UL (US version)	CE (European version) or UL (US version)
Cutting accuracy	±0.1 mm (Single cut), ±0.18 mm (Double cut) in paper feed direction	± 0.15 (Single Cut)

^{* 1:}Applicable paper thickness is effective for short grained paper only.

- Specifications are subject to change without notice.
- *2:For range 321-350g / m² and 0.31-0.35mm thick, subject to no-continuous and light-duty use.

EU Version

No.1	No.2	No.3	No.4	No.5	No.6
Slitter B90 12 90 6 90 12 111 15	Slitter B90 12 90 6 90 12 7	Slitter B90 12 90 6 90 12 13 55 17 55 18 6 85 17 19 55 17 85 6 85 17 18 55 17 85 6 85 17 18 55 17 85 6 85 17	Slitter B90 12 90 6 90 12 7 1	Sitter B90 12 90 6 90 12 95 6 90 12 95 7 9 9 9 12 95 7 9 9 9 9 12 95 9 9 9 12 95 9 9 12 95 9 9 12 95 9 9 12 95 9 9 12 95 9 9 12 95 9 9 12 95 9 12 96 90 12 97 90 12 98 90 12 9	Slitter B90 12 90 6 90 12 13.5 54 54 54 54 54 554 554 554
Slitter S 14	Slitter S 14 91 91 14 7 55 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Slitter S 14 91 91 14 155 91 14 17 91 14 17 91 14 17 91 14 17 91 14 17 91 14 17 91 14 18 91 14 19 91 14 1	Slitter S 14 91 91 14 7 151 91 14 7 151 91 14 7 151 91 14 7 151 91 14 7 151 91 14 7 151 91 151 7 151 91 151 7 151 91 151 7 151 91 151 7 151 91 151 7 151 91 151 7 151 91 91 14 Perfo	Slitter S 14 91 91 14 9.31 91 14 9.31 91 14 9.31 91 14 9.31 91 14 9.31 91 14 9.31 91 14 9.31 91 14 9.31 91 14 9.31 91 14 9.31 91 91 14 9.31 91 91 14 9.31 91 91 14 9.31 91 91 14 9.31 91 91 91 14 9.31 91 91 91 91 91 91 91 91 91 91 91 91 91	Slitter S 14 91 91 14 13.5 54 54 54 54 54 54 54 54 54
No.7	No.8	No.9	No.10	No.11	No.12
Slitter B90 12 90 6 90 12 144 154 155 158 158 159 17 85 6 85 17 144 159 159 150 17 85 6 85 17 150 150 150 150 150 150 150 150 150 150	Slitter HD 105 105 148.5 Slitter FD 210 148.5 Slitter FP 155 55	Slitter HD 105 105 99 99 Slitter FD 210 99 99 Slitter FP 155 55	Slitter HD 105 105 74.25	Slitter P1 131 88.9 6 88.9 13.1 127 127 127 13 Slitter P2 14 17 16 16 17 17 127 13 17 127 13 18 16	15 Slitter PC 30.8 148.5 30.7 14 105 60 105 14
54 18 54 18 54 13 Scoring	148.5 148.5 Perio	99 99 99 Perto	74.25 74.25 74.25 74.25 Perfo	Patterns mark square lines countries solitters solitters solversaTrim as solve	an be cut by supplied with
Slitter P 14 127 55 14 14 128 18 54 18 54 18	Slitter SD 105 105 148.5	Slitter SD 105 105 99 99 99	Slitter SD 105 105 74.25 74.25 74.25	Patterns maked can be cut by BC- (You are able slitter B90 or E purchase BC-10	-10 as standard. to choose the B85 when you



