

# → IDEAL 6550-95 EP

## PROGRAMMABLE GUILLOTINE

650 mm cutting length | electro-mechanical blade drive | automatic clamping system (clamp can be lowered or raised independently from blade) | power backgauge with fully programmable "EP" backgauge control module and digital measurement readout | digital display for measurement readout in cm or inches (display accurate to 1/10 mm or 1/100 inch) | 10-button key pad for presetting of measurement | memory key for repeat cuts | programmable "EP" backgauge control module for 9 programs with 9 steps in each program (up to 9 repeat cuts can be integrated into a program as one single program step) | setting of program steps via "Start" button | "SET" function key for reference measurement | programmable EJECT function - for pushing out the paper | two programmable keys for quick setting of frequently needed measurements | self-diagnosis system with error indication on display | electronic hand wheel for manual backgauge positioning with infinitely variable speed control (from very slow to very fast) | optical cutting line | clamp guided on both sides for evenly distributed clamping pressure | spindle guided backgauge for precise positioning | adjustable backgauge with narrow separations and plastic gliders | two side lays each on front and rear tables | solid steel blade carrier and adjustable blade guides | comprehensive IDEAL safety package as described on pages 8/9 | complete with stand and storage shelf

Power supply: 230 V / 50 Hz / 1~<sup>1</sup>, Motor performance (input capacity): blade drive 1.1 kW, clamp drive 0.32 kW, backgauge drive 0.1 kW, Dimensions (H x W x D): 1220 x 995 x 1260 mm, Weight: 304 kg, Colour: pearl grey.

<sup>1</sup> other voltages available



## "EP" BACKGAUGE CONTROL



9 programs with 9 steps in each program can be stored in the "EP" backgauge control module. A memory key is available for repeat cuts.

## ELECTRONIC HAND WHEEL



The electronic hand wheel with infinitely variable speed (from very slow to very fast) allows manual setting of the backgauge.

## OPTICAL CUTTING LINE



The optical cutting line facilitates alignment of cutting marks and guarantees precise cuts.

## → IDEAL 6550-95 EP

Cutting length	650 mm
Cutting height	80 mm
Narrow cut	25 mm
Table depth	610 mm
Power supply	230 V / 50 Hz <sup>1</sup>